

| (中国产) 型号 MMD-UP | | 0051 M(P)HY-C | 0071 M(P)HY-C | 0081 M(P)HY-C | 0091 M(P)HY-C | 0101 M(P)HY-C | 0121 M(P)HY-C | 0141 M(P)HY-C | 0151 M(P)HY-C | 0171 M(P)HY-C | 0181 M(P)HY-C | 0201 M(P)HY-C | 0241 M(P)HY-C | 0271 M(P)HY-C | | | | |
|-----------------|--------------|-------------------------|---------------------|------------------|------------------|-------------------------|------------------|---------------------|--------------------|------------------|-------------------------|---------------------|-------------------------|------------------|---------------------|----------------|-----------------------|---------------------------|
| 制冷量 | (kW) | 1.7 | 2.2 | 2.5 | 2.8 | 3.2 | 3.6 | 4.0 | 4.5 | 5.0 | 5.6 | 6.3 | 7.1 | 8.0 | | | | |
| 制热量 | (kW) | 1.9 | 2.5 | 2.8 | 3.2 | 3.6 | 4.0 | 4.5 | 5.0 | 5.6 | 6.3 | 7.1 | 8.0 | 9.0 | | | | |
| 电源 | | 单相220V 50Hz | | | | | | | | | | | | | | | | |
| 启动电流 | 不带泵/带泵 (A) | 0.25/0.27 | 0.29/0.31 | | 0.31/0.33 | | 0.33/0.34 | | 0.37/0.38 | | 0.39/0.41 | | 0.58/0.59 | | 0.62/0.64 | | | |
| 耗电量 | 不带泵/带泵 (kW) | 0.027/0.031 | 0.032/0.036 | | 0.034/0.038 | | 0.036/0.040 | | 0.040/0.044 | | 0.042/0.046 | | 0.066/0.070 | | 0.071/0.075 | | | |
| 运行电流 | 不带泵/带泵 (A) | 0.43/0.47 | 0.51/0.54 | | 0.54/0.58 | | 0.58/0.60 | | 0.65/0.67 | | 0.68/0.72 | | 1.02/1.03 | | 1.09/1.12 | | | |
| 外形尺寸 | 高/宽/深 (mm) | 210/700/450 | | | | | | 210/900/450 | | | | 210/1100/450 | | | | | | |
| 重量 | 不带泵/带泵 (Kg) | 15/15 | | | | | | 18/19 | | | | 21/22 | | | | | | |
| 标准风量 | (m³/h) | 450/430/ 410/400/380 | 540/510/470/420/400 | | | 570/540/ 500/450/430 | | 600/570/520/480/440 | | | 630/590/ 550/500/470 | | 690/660/ 640/600/550 | | 780/770/760/670/660 | | 1080/1030/950/910/860 | 1140/1060/ 980/940/910 |
| 机外静压 | (Pa) | 10(min) - 45(max)* | | | | | | | | | | | | | | | | |
| 控制器 | | 选配 | | | | | | | | | | | | | | | | |
| 连接管道 | 气管 (mm) | φ9.5 | | | | | | φ12.7 | | | | φ15.9 | | | | | | |
| | 液管 (mm) | φ6.4 | | | | | | | | | | | | | | | | |
| | 排水口 (mm) | 25 | | | | | | | | | | | | | | | | |
| 运转音 | dB(A) | 30/29/ 28/27/26 | 31/30/29/27/26 | | | 32/31/29/28/27 | | | 33/32/ 31/29/28 | | 34/33/ 32/30/29 | | 35/34/33/31/30 | | | 36/35/33/32/31 | | 37/35/ 34/33/32 |
| 3D立体导风板(选配) | 型号 | TCB-TDL0141SDY-C | | | | | | TCB-TDL0181SDY-C | | | | TCB-TDL0271SDY-C | | | | | | |
| | 尺寸高/宽/深 (mm) | 180/810/70(面板厚度10) | | | | | | 180/1010/70(面板厚度10) | | | | 180/1210/70(面板厚度10) | | | | | | |