

(中国产) 型号 MMD-UP		0051	0071	0081	0091	0101	0121	0141	0151	0171	0181	0201	0241	0271	
		M(P)HY-CT	M(P)HY-CT	M(P)HY-CT	M(P)HY-CT	M(P)HY-CT	M(P)HY-CT	M(P)HY-CT	M(P)HY-CT	M(P)HY-CT	M(P)HY-CT	M(P)HY-CT	M(P)HY-CT	M(P)HY-CT	
制冷量	(kW)	1.7	2.2	2.5	2.8	3.2	3.6	4.0	4.5	5.0	5.6	6.3	7.1	8.0	
制热量	(kW)	1.9	2.5	2.8	3.2	3.6	4.0	4.5	5.0	5.6	6.3	7.1	8.0	9.0	
电源		单相220V 50Hz													
启动电流	不带泵/带泵 (A)	0.25/0.27	0.29/0.31	0.31/0.33	0.33/0.34	0.37/0.38	0.35/0.37	0.39/0.41	0.58/0.59	0.62/0.64					
耗电量	不带泵/带泵 (kW)	0.027/0.031	0.032/0.036	0.034/0.038	0.036/0.040	0.040/0.044	0.036/0.040	0.042/0.046	0.066/0.070	0.071/0.075					
运行电流	不带泵/带泵 (A)	0.43/0.47	0.51/0.54	0.54/0.58	0.58/0.60	0.65/0.67	0.61/0.65	0.68/0.72	1.02/1.03	1.09/1.12					
外形尺寸	高/宽/深 (mm)	210/700/450						210/900/450				210/1100/450			
重量	不带泵/带泵 (Kg)	15/15						18/19				21/22			
标准风量	(m³/h)	450/430/ 410/400/380	540/510/470/420/400	570/540/ 500/450/430	600/570/520/480/440	630/590/ 550/500/470	690/660/ 640/600/550	780/770/760/670/660	1080/1030/950/910/860	1140/1060/ 980/940/910					
机外静压	(Pa)	10(min) - 45(max)*													
控制器		选配													
连接管道	气管 (mm)	φ9.5						φ12.7				φ15.9			
	液管 (mm)	φ6.4											φ9.5		
	排水口 (mm)	25													
运转音	dB(A)	30/29/ 28/27/26	31/30/29/27/26	32/31/29/28/27	33/32/ 31/29/28	34/33/ 32/30/29	35/34/33/31/30	36/35/33/32/31	37/35/ 34/33/32						
3D立体 导风板 (选配)	型号	TCB-TDL0141SDY-C						TCB-TDL0181SDY-C				TCB-TDL0271SDY-C			
	尺寸高/宽/深 (mm)	180/810/70(面板厚度10)						180/1010/70(面板厚度10)				180/1210/70(面板厚度10)			